







HOME **BIKES** DEALERS ABOUT US TEAM SUPPORT VIDEO PHOTOS STORE

TR500 PATROL SUPPRESSOR SCOUT SMUGGLER RIPCORD TRANSAM BLT PBJ RAPTURE KLUNKER







RAPTURE OVERVIEW

Anything that involves beer drinking, cow bells and, turning yourself inside out in the worst condition imaginable, we fully support. After several years racing the classic PNW races, we've taken a few things learned out there in the mud to develop our own race bred shredding machine called the Rapture. We believe that "steel is real" and in "one ring, suffer-ring." but if you're into more gears we've got you covered too. Our custom FAST (Freedom Axle System Technology) dropout allows for singlespeed or geared builds. The system also allows for quick singlespeed wheel changes on race day which eliminates the need for a pit bike. Other features include a 44mm tapered fork compatible headtube and clean internal cable routing. We'll leave the choice to wear a skin-suit or crazy costume up to you, but when it comes to getting from point A to B over mixed terrain as fast as possible, we've proven with multiple wins that the Rapture is a force

to be reckoned with.

44mm Headtube Fits Tapered Steerer Tube Carbon Forks (ENVE, etc)
High End Founderland Co. Butted 4130 Chromoly
User Friendly Threaded 68mm Bottom Bracket Shell
Removable Downtube Cable Stops
Internal Rear Brake Routing in Top Tube
Includes Color Matched 4130 Chromoly Disc Fork 11/8" Steer

Frame Weight: 4.56 lbs./ Fork Weight: 2.23 lbs.



View Geometry in MILLIMETERS / INCHES

	SM	MD	LG	XL	
Reach	365	377	391	406	
Stack	534	548	581	595	
Effective TopTube	520	545	570	600	
SeatTube	480	520	550	580	
SeatTube Angle	73	73	73	73	
HeadTube Length	122	130	150	170	
HeadTube Angle	71	72	72	72	
Chainstay	426	426	426	426	
Wheelbase	995	1011	1027	1046	
BB Drop	67	67	67	67	
stimated BB Height	281	281	281	281	

NEED, HELP PICKING A SIZE? CHECK OUT OUR SIZE GUIDE HERE.

FRAMESET WITH FORK

\$599 USD*

FRAME SPECS

Fork Axle To Crown	395mm
Fork Offset	45mm
Headset (Top)	44mm Zero Stack
Headset (Bottom)	44mm External
BB Shell	68mm BSA Threaded
Rear Brake Mount	160mm IS Mount
Rear Axle	10 x 135mm
Front Derailleur Style	28.6mm Bottom Pull
ISCG Tabs	None
Seatpost Diameter	27.2mm
Seat Clamp	29.8mm
Max Chainring Size	42t Single / 50/34t Double
Max Tire Size	700c x 35c

^{*}Prices are shown for the United States only. Prices vary for countries outside the United States.