

Repeater NX Suspension Guide

Before you make adjustments, begin with all compression and rebound knobs in their fully-closed, clockwise position. Count all clicks in a counterclockwise direction from there. When checking sag make sure all compression levers and lockout mechanisms are in their fully open (counter-clockwise) position.

We don't recommend using sag measurements to set up suspension forks. You should aim for a balanced feel between the front and rear suspension. Check the o-ring located on your fork during the first few rides to ensure you aren't using too much or too little of your travel and adjust accordingly.

Fork: RockShox ZEB R, 160mm, 44mm Offset, 1.8 taper, 2 Volume Spacers, 148psi Max				
			Compression	Rebound
Rider Weight (lbs)	Rider Weight (kgs)	Suggested Pressure (psi)	Low Speed	Low Speed
120-140	54-64	55-64	N/A	9
140-160	64-73	64-72	N/A	8
160-180	73-82	72-80	N/A	7
180-200	82-91	80-88	N/A	6
200-220	91-100	88-97	N/A	5
220-240	100-109	97-102	N/A	4
240-260	109-118	102-108	N/A	3

Rear Shock: Fox Float X Performance 2-Position, 205mm x 65mm, 0.7 Volume Spacer, 350psi Max				
Rear Shock Sag: 18-22mm (28-34%)				
Shock Tune: CMSSAL001, PRMAL001, Rezi LLB3			Compression	Rebound
Rider Weight (lbs)	Rider Weight (kgs)	Suggested Pressure (psi)	Low Speed	Low Speed
120-140	54-64	135	N/A	10
140-160	64-73	145	N/A	9
160-180	73-82	165	N/A	9
180-200	82-91	195	N/A	9
200-220	91-100	215	N/A	8
220-240	100-109	235	N/A	8
240-260	109-118	255	N/A	7